



**TYPICAL HALF-SECTION
FLEXIBLE PAVEMENT WIDENING**

- ① EXISTING PAVEMENT BUILD-UP ~ THICKNESS VARIES
- ② EXISTING AGGREGATE BASE ~ THICKNESS VARIES
- ③ ITEM 253 ~ PAVEMENT REPAIR – REPLACE WITH ALLEN COUNTY ENGINEER APPROVED PAVEMENT BUILD-UP
- ④ SEE ALLEN COUNTY STD. DWG. PF-3, PF-4 OR PF-6 FOR FLEXIBLE PAVEMENT THICKNESSES AND SPECIFICATIONS
- ⑤ ITEM 304 ~ SEE ALLEN COUNTY STD. DWG. PF-3, PF-4, OR PF-6 FOR THICKNESS
- ⑥ ITEM 204 ~ SUBGRADE COMPACTION, ODOT ITEM 204 SPECS.
- ⑦ ITEM 605 ~ 8" AGGREGATE DRAINS (12" WIDE SPACED 50' ON A SIDE & 25' FROM THE NEAREST DRAIN ON OPPOSITE SIDE.)
- ⑧ ITEM 659 ~ SEEDING AND MULCHING, USE SEEDING MIXTURE APPROVED BY THE ALLEN COUNTY ENGINEER.

6" MIN. DIA. DRAIN TILE (BOTH SIDES OF STREET) (706.06, 706.07, 706.08, 706.09, 707.33 (PERFORATED), 707.41 (PERFORATED)) OR AS SPECIFIED BY THE ALLEN COUNTY ENGINEER. ODOT TYPE 4 BEDDING. LOT DRAINS MAY BE CONNECTED TO DRAIN TILE, ONLY IF TILE HAS BEEN SIZED BY A PROFESSIONAL ENGINEER TO HANDLE ADDITIONAL FLOW.

- NOTE: 1. SEE ALLEN COUNTY STD. DRWG. DW-2 OR DW-3 FOR DRIVEWAY CONSTRUCTION.
3. ROADSIDE DITCH SHALL NOT BE FILLED IN.
4. STORM SEWERS SHALL BE LOCATED WITHIN THE ROAD RIGHT-OF-WAY.

THE ITEMS LISTED ABOVE REFER TO THE MATERIAL & CONSTRUCTION SPECIFICATIONS FOUND IN THE LATEST EDITION OF THE OHIO DEPARTMENT OF TRANSPORTATION CONSTRUCTION & MATERIAL MANUAL UNLESS NOTED OTHERWISE.

REVISIONS			ALLEN COUNTY, OHIO	
NO.	DATE	BY	COUNTY ENGINEER	
1	1-16-13	RJM	PAVEMENT - FLEXIBLE WIDENING TYPICAL SECTION	
2	5-16-16	ZJG		
			STANDARD CONSTRUCTION DRAWING PF-7 DRAWN BY: Z.J.G. APPROVED BY: B. E. RHODES	