



NOTES

1. THE DESIGN DETAILS SHOWN HEREON SHALL GOVERN THE CONSTRUCTION OF CURBS UNLESS OTHERWISE SHOWN ON PROJECT PLANS.
2. CONCRETE SHALL BE CLASS "QC1".
3. MAXIMUM SPACING FOR CONTRACTION JOINTS SHALL BE 10 FEET.
4. EXPANSION JOINTS SHALL BE PLACED A MAXIMUM OF 200 FEET APART.
5. TYPE "SG" OR TYPE "W" MAY BE USED WITH NEW CONSTRUCTION. TYPE "RG" IS FOR USE WITH REPLACEMENT SECTIONS ONLY.

| REVISIONS |          |     | ALLEN COUNTY, OHIO   |  |
|-----------|----------|-----|--|--|
| NO.       | DATE     | BY  | COUNTY ENGINEER  |  |
| 1         | 6-3-76   | TJP | <b>CURB, COMBINATION CURB &amp;<br/>GUTTER - CONCRETE TYPE<br/>"SG", "RG", &amp; "W"</b><br>STANDARD CONSTRUCTION DRAWING CC-1<br>DRAWN BY: Z.J.G. APPROVED BY: B. E. RHODES |  |
| 2         | 7-1-76   | TJP |  |  |
| 3         | 6-4-79   | TJP |  |  |
| 4         | 10-5-06  | RJM |  |  |
| 5         | 1-16-13  | RJM |  |  |
| 6         | 5-12-16  | ZJG |  |  |
| 7         | 01-01-23 | ZJG |  |  |